


Griezums 2-2
TS-2, PK 2+15

Diagram showing a cross-section of a road with a central drainage ditch. The road width is 2.50m, and the ditch width is 2.98m. The ditch depth is 0.15m, and the road surface height is 9.00m. The ditch is filled with gravel (1.10m) and has a 1:2 slope. The road is constructed with AC8 asphalt (5cm), mineral material (20cm), and subgrade (30cm). The ditch is labeled "Esošais augstspiediena gāzesvads".

Karstais asfalts AC8 surf, h=5cm, SIII
Minerālmateriālu maisījums (0/45), h=20 cm, SIII
Salizturīgā kārtā, h(vid)=30 cm
Uzbēruma grunts, h(vid)=1.10m
Esošā grunts (sabīvēta)

Pasūmājs:			Objekts:					
Mārupes novada Dome Daugavas iela 29, Mārupe, Mārupes novads LV - 2167			<i>Mazcenu alejas pārbūve</i> Ietves izbūve no Loka ceļa līdz Jaunmārupes pamatskolai		SIA "BM - projekts" Viršu iela 12-47, Tirane Mārupes novads, LV - 2167			
			Adrese:		Līguma nr.: 18.09.2015-2 Arhīva nr.: 18.09.2015-2 M b/m			
			Mazcenu aleja posmā no Loka ceļa līdz					
			Jaunmārupes pamatskolai					
			Lapas nosaukums:					
			Griezumī					
Būvpr. daļ. vad.	D. Dāle	14.09.2018.			Stadija		Marka	Ras. Nr.
Izstrādāja	D. Dāle	14.09.2018.			BP		TS-CD	2